

Technical Data Sheet

Issue date: 05/01/2005 Date last modification: 12/12/2016

GRAPHICS - Mounting Films

4-GL2B-03748 MONOTAPE 940P CLEAR ASP2 PERMANENT/ASP2 PERMANENT WKPE90

Adhesive

Solvent based permanent acrylic adhesive featuring low cohesion and very high adhesion to a wide variety of substrates, including slightly rough surfaces. Suitable for mounting tapes.

Reference ASP2 permanent Type Acrylic permanent

Min. Appl. Temp. +5°C

Service Temp. -30°C/+120°C

Shear Low

Tack Very High N/inch² Final Adhesion High N/inch

Face Material

Self-wound construction with a clear polyester carrier.

Type Polyester Colour and Finish Clear

Weight 17 g/m 2 ±10% ISO-536 Thickness 12 μ ±10% ISO 534-80

Adhesive

Solvent based permanent acrylic adhesive featuring low cohesion and very high adhesion to a wide variety of substrates, including slightly rough surfaces. Suitable for mounting tapes.

Reference ASP2 permanent Type Acrylic permanent

Min. Appl. Temp. +5°C

Service Temp. -30°C/+120°C

Shear Low

Tack Very High N/inch² Final Adhesion High N/inch

Liner

Type Two side silicone coated two

side PE coated Kraft

Colour and Finish White

Weight 90 g/m² ±10% PP-032 - ISO

536

Thickness 100 μ ±10% ISO 534 Transparency n.a. % DIN 53 147-64

Applications

For photographic and digital mounting.

Printing Methods

Not printable.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the following **STORAGE CONDITIONS**:

- This material must be stored at a temperature of $22^{\circ}\text{C} \pm 2^{\circ}\text{C}$ and 50 \pm 5% of Relative Humidity.
- Storage area must be dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

All Ritrama products are subject to strict manufacturing controls to guarantee good quality products. The above information is based on research believed to be reliable, but does not constitute a warranty. All material should be tested by the purchaser to determine suitability of the product for their purposes.

All information is subject to change without prior notice.





